



SG 4

Managing many users is now easier with the SG 4. This gateway enables large venue owners to manage their network easily with self-service account provisioning and multiple authentication methods. It offers intelligent and dynamic traffic management, flexible time and/or volume accounting—all these in one box.



Standard Features

Plug & Play Zero Configuration Network

- Supports static and dynamic (DHCP) IP addresses
- Supports selective DHCP scope per VLAN
- Adaptive Domain Name Services (DNS)
- Transparent Simple Mail Transfer Protocol (SMTP)
- Transparent web proxy
- Application NAT (VPN, SIP, RSTP, MMS, H323)
- IPv6 support

Performance Features

- Supports up to 30,000 users
- 1000 DNS QPS
- Support 10GE network card

Guest Management & Content

- Auto-logout of inactive guests
- Forced logout of guests
- Departed device detection and logout
- Bandwidth rate limit: device / account
- HTTP / HTTPS / IP walled garden
- Email login reminder
- Smartphone / tablets friendly
- Location / VLAN-based content delivery
- Unique login pages for separate locations
- Admin-assisted login

Multiple Authentication & Billing Interfaces

- Complimentary access
- User ID and password authentication (local accounts)
- Access code authentication (local accounts)
- MAC-level authentication for non-HTTP devices
- PMS authentication and Billing
- LDAP authentication
- Email / SMS authentication
- Social Media: Facebook, Twitter, Google+, Instagram, Line, WeChat
- Auto-login (no login page)
- Account Printer support

PMS Support

- TCP/IP: Micros Fidelio / Opera, Enhanced Opera extensions, Galaxy Lightspeed
- Serial: Micros Fidelio / Opera, FCS, Softbrands, Hobic, Prologic, Control, Protel, Agilysys.

Credit Card Authentication & Billing

- Worldpay, Authorize.net, Payflow Pro, Payflow Link

Concurrent / Multi Business Model Support

- Unlimited duration and volume
- Fixed duration
- Stored duration
- Stored volume: 2 modes (logout / throttled)

Guest-Aware Bandwidth Optimization

- Application traffic prioritization
- Guest-aware Advanced QoS (Basic / Premium / Guaranteed)
- Shared bandwidth rate limit across multiple devices
- Volume control

RADIUS / WISPr

- RADIUS authentication and billing
- Support for Wireless Internet Service Provider roaming

Lawful Intercept

- Monitoring of networks
- Comply with legislative requirements
- Local storage of logs

Security & Reporting

- Personal Area Network (PAN)
- URL filtering
- Access control to web administration GUI
- MAC-based blacklist
- Anti-Spam and Anti-DoS features
- DoS event alerts
- Configurable plan-based firewall
- 802.1Q VLAN security
- Web session rate limit
- Real-time reporting on authenticated guest and detected devices
- Guests, device and web-page access logging
- Graphical presentation of system reports

Reliability

- High Availability Offering (Active-Passive)
 - Real-time HA disk replication
 - Fail-over within 1 minute, typically 30 seconds
- Configuration Backup and Restore Function
- Redundant Power Supply
- Redundant Array of Inexpensive Disks (RAID)
- Dedicated LAN, WAN, HA, Management and WAN2 ports with active-passive link redundancy support
- Built-in remote KVM
- Dual WAN link load-balancing

System Management & Administration

- Supports SNMPv2
- Network Time Protocol (NTP) server
- Configurable DHCP server / relay
- Remote Syslog
- User-provisioned routable public IP address
- External HTTP web proxy
- Remote edge device (switches / hubs / access points) monitoring
- Multiple IP for Network Address Port Translation (NAPT)
- Secure Socket Layer (SSL) certificate management
- Two-tier console CLI support via SSH
- Configurable tiered access for web admin
- Admin access audit logs
- DNS Hosting
- ANTLabs Cloud Services (ACS) support

Event Scheduling

- Preschedule events
- Visitor digital experience customization
- Event reports generation



Specifications

Model	SG 4	
	4210	4400
Default User License ¹	3000	3000
Max User License	10,000	30,000
VLANs	4000	
Max Throughput ²	974 Mbps (1GE NIC) and 9 Gbps (10GE NIC)	
Max PPS	200,000	250,000
Supported NIC Interfaces	10/100/1000/10000 Base-T/10000 Fiber	
Network Interfaces	2 x LAN Port (bonded) 2 x WAN Port (bonded) 2 x WAN2 Port (bonded) 2 x Management Port (bonded) 2 x HA Port (bonded) 2 x DMZ Port (bonded)	
COM	1 x RS232 (DB9) Console Port	
Power Supply	2 x 750W; auto-ranging (100V~240V)	
Weight	Actual unit: 16.5 kg Shipping: 26.6 kg	Actual unit: 17 kg Shipping: 27.1 kg
Dimensions	1U Actual unit: 482.43 (W) x 758.23 (D) x 42.8 (H) mm Shipping: 616 (W) x 919 (D) x 279 (H) mm	
Remote Management	1 x Network Remote Management KVM Port	
Certifications	SCC, CNCA or CCC, CE, TUV, IECCE CB, KSA ICCP, NRCS, BSMI, NRTL, ACMA or C-Tick, ICES, VCCI, GS, GOST, SABS, KCC, FCC, ICT	
Included Modules	LDAP Authentication, RADIUS Authentication, Volume Control, Advanced QoS, Management Port, Multi-WAN, SMS via SMPP	
Add-on Modules		
Property Management System	✓	
Payment	✓	
High Availability	✓	
Account Printer Support	✓ Max 40	
Lawful Intercept	✓ Syslog + Local	
10 GE Interface Support	✓	
Event Manager	✓ 30 Events	
Personal Area Network	✓	

¹ Detected Devices

² As defined by RFC1242, Section 3.17